

CACTUS 10

DRIES RESIN IN 30 MINUTES!



Description:

The Cactus 10 will process up to 18 lbs/hr of most engineering resins.

The Cactus dryer is mounted directly on the feed throat of the molding machine. A hopper or loader is mounted to the top of the dryer to provide a continuous supply of resin to the dryer. The resin is supplied directly from the bag, barrel or gaylord and does not require pre-drying

Technical Data:

Height	(in)	28
Ship Weight	(lbs)	47
Air Consumption	(cfm)	1.5
Electrical	(kw)	1.36
230V, 1 Phase	(amps)	5.9
Heated Capacity	(lbs)	3.5
Total Capacity	(lbs)	5

THROUGHPUT GUIDE LBS/HR

ABS	18
ACETAL	45
ACRYLIC	18
BUTYRATE	9
NYLON	18
PBT (VALOX)	18
PET (RYNITE)	9
POLYCARBONATE	18
POLYETHYLENE	45
POLYSTYRENE	45
POLYSULPHONE	9
POLYURETHANE	9
PPO (NORYL)	18
ULTEM	9
PVC	18
SAN	18

CACTUS MACHINERY LLC. - 1570 Georgetown Rd.
Hudson, OH 44236 PN:330-650-9280 FX: 330-653-3052
Web: www.cactusmachinery.com
E-mail: sales@cactusmachinery.com

